

Model	Type or Tap loss	Insertion loss (dB, max)				Out to tap (dB, min)			
		5-65 MHz	65-550 MHz	550-750 MHz	750-1000 MHz	5-65 MHz	65-550 MHz	550-750 MHz	750-1000 MHz
SPLITTERS									
GLSP-2		4.5	4.2	4.9	5.5	25	25	22	22
GLSP-3		7.5	6.8	7.2	7.9	25	25	22	22
GLSP-3UNB(H)		4.3	4.5	4.9	5.5	25	25	22	22
GLSP-3UNB(L)		7.5	6.8	7.2	7.9	25	25	22	22
ONE WAY DIRECTIONAL COUPLERS									
GLDC-8	8	2.7	2.5	2.7	3.0	25	25	22	22
GLDC-10	10	2.5	2.3	2.5	2.7	25	25	22	22
GLDC-12	12	2.2	2.0	2.2	2.5	25	25	22	22
GLDC-14	14	1.9	1.7	2.1	2.2	25	25	22	22
GLDC-16	16	1.7	1.5	1.9	2.1	25	25	22	22
GLDC-18	18	1.6	1.4	1.8	2.0	25	25	22	22
GLDC-20	20	1.6	1.4	1.8	2.0	25	25	22	22
TWO WAY DIRECTIONAL COUPLERS									
GLDC-8	8	4.0	4.0	4.5	4.5	25	25	22	22
GLDC-10	10	3.3	3.3	3.7	3.7	25	25	22	22
GLDC-12	12	2.5	2.5	2.9	2.9	25	25	22	22
GLDC-14	14	2.3	2.3	2.7	2.7	25	25	22	22
GLDC-16	16	2.0	2.0	2.5	2.5	25	25	22	22
GLDC-18	18	2.0	2.0	2.5	2.5	25	25	22	22
GLDC-20	20	1.7	1.5	2.0	2.0	25	25	22	22
POWER INSERTER						RF to AC isolation*(dB)			
GLPI		0.4	0.3	0.4	1.2	60	60	60	60

SPECIFICATIONS:

- Return loss all ports: 5-1000MHz, 18dB min
- Hum modulation at 10 Amps: 70dB min
- All port power passing: 10 Amps 60VAC
- Impedance: 75 all ports

